| } | • | | | | _ | | | | | |
|--|---|-------|------------------|---------|----------------------|----------|---------------------------------------|--|--|--|
| | | · · · | CLASSIFIE | MESSAGE | -0 | R | OUTING . | | | |
| ORIG : UNIT : EXT : DATE : Z7 | / NOV /U | | TOP SEC TAGBO | 7. | 3 | 5.j. e | 5, 50 | | | |
| TO : FROM: CONF: | | | | | P.R.E.C.E.D.E.N.C.E. | DEFERRED | X PRIORITY AND S OPERATIONAL INITIALS | | | |
| INFO: | PAGE 1 OF | 3 | | | ÖE | ROOTINE | UU [71280 | | | |
| то | | | INFO | | | | 9881 | | | |
|] | REF: TELECON FOLLOWING INFO AS CONTAINED IN MSG 7229 152241Z OCT 69 IS RETRANSMITTED FOR YOUR GUIDANCE: QUOTE: SUBJECT: USE OF THE UNIVERSAL GRID AND TITLING INSTRUCTIONS FOR 335A/B PHOTOGRAPHY | | | | | | | | | |

- 1. IT IS REQUESTED THAT MANOR ADVISE ALL POTENTIAL USERS, INCLUDING PROCESSING FACILITIES, OF THESE INSTRUCTIONS.
- 2. THE "INSTRUCTIONS FOR THE USE OF THE UNIVERSAL GRID WITH 335A/B PHOTOGRAPHY" WILL BE INCLUDED AS AN INTEGRAL PART OF THE HEAD IDENT OF THE ORIGINAL NEGATIVE ON EACH ROLL OF PHOTOGRAPHY IN WHICH THE 335A/B CAMERA SYSTEM IS USED AS THE MISSION SENSOR. THE INSTRUCTION SHOULD BE SPLICED BETWEEN THE HEAD IDENT AND THE FIRST FRAME OF PHOTOGRAPHY ON EACH ROLL, IT SHOULD BE OF SUFFICIENT LENGTH (15 TO 18 INCHES) TO PREVENT THE SPLICE FROM TOUCHING THE NEGATIVE WHEN THE NEGATIVE IS ROLLED ON THE SPOOL. THE INSTRUCTIONS SHOULD BE RIGHT READING.

RELEASING OFFICER

TOP SECRET

AUTHENTICATING OFFICER

REPRODUCTION BY OTHER THAN THE ISSUING OFFICE IS PROHIBITED. Copy No.

Signal Center Transmission Copy - DO NOT DETACH - Forward with Master

Approved For Release 2008/11/24 : CIA-RDP78B03824A001100020013-9 |

25X1

25X1 25X1

25X1

25X1

| | 25X | |
|---|--------------|--|
| | 25X | |
| 2 | 5 X 1 | |

| | | App | roved F | or Relea | ase 2008/11/24 : CIA-RDP78B | 0382 | 4A001100020 | 013-9 | |
|---------------------------|----------|------|---------|----------|-----------------------------|----------|-------------|--------------------------|----------|
| | ₩. | ŧ | • | | CLASSIFIED MESSAGE | | RC | OUTING | |
| ORIG : UNIT : EXT : | | | | | TOP SECRET TAGBOARD | 2 3 | | 5 6 | |
| DATE : | | | | | | | | | |
| TO : FROM: | | | | | | P | DEFERRED | PRIORITY | INITIALS |
| CONF: | | ** | | | ia | #CEC#2C# | ROUTINE | OPERATIONAL IMMEDIATE | INITIALS |
| INFO: | | | | | | <u> </u> | | | |
| | PAGE 2 (|)F 3 | | | | | | | |
| 70 | | | | INF | 0 | | CITE | | |

3. INSTRUCTIONS WERE FORMATED AND COPIED AT NEGATIVES AND FOR REPRODUCTIONS. WILL FORWARD A SUPPLY POSITIVES WERE SENT TO TO ALTERNATE PROCESSING FACILITIES ON DIRECTION FROM THE INSTRUCTIONS READ AS FOLLOWS:

INFO

"INSTRUCTIONS FOR THE USE OF THE UNIVERSAL GRID 335A/B CAMERA SYSTEM. PLACE THE FILM ON THE LIGHT TABLE SO THAT THE TITLING IS UPRIGHT AND READABLE. PLACE THE GRID OVER THE FILM WITH THE LETTERING AND NUMBERING UPRIGHT AND READABLE. ALIGN X-0 ALONG THE LEFT EDGE OF THE FORMAT. ALIGN Y-0 ALONG THE BOTTOM EDGE OF THE FILM (NOT THE FORMAT). READ AND REPORT COORDINATES IN THE USUAL MANNER, TO THE RIGHT AND UP. EXAMPLE: X-18.0/Y-23.5 INDICATES THE APPROXIMATE POSITION OF THE 24 HOUR CLOCK."

- 4. THE 335A/B CAMERA SYSTEM ACQUIRES 9 X 9 INCH FORMATS ON 9.5 INCH WIDE FILM. THERE IS A 0.25 INCH BORDER ALONG EACH EDGE OF THE FILM.
- 5. THE ORIGINAL NEGATIVE MUST BE TITLED ON THE EMULSION WITH TEN POINT TYPE. THE TITLING MUST BE PLACED IN THE BORDER CONTAINING THE 24 HOURS CLOCK WITH THE TITLING READABLE WHEN THE CLOCK IS READABLE.

COORDINATING OFFICERS

RELEASING OFFICER

то

AUTHENTICATING OFFICER

REPRODUCTION BY OTHER THAN THE ISSUING OFFICE IS PROHIBITED. COPY No. Signal Center Transmission Copy - DO NOT DETACH - Forward with Master

Approved For Release 2008/11/24: CIA-RDP78B03824A001100020013-9

| ā | • | , A | pproved For Release 2008/11/24 : CIA- | RDP78 | B038 | 324/ | 40011000 • | 200 | 13-9 | | | | |
|-----------------|--------------------|------|---------------------------------------|----------|-----------|------|---------------|-----------|-------------|----------|--|--|--|
| ORIG : | CLASSIFIED MESSAGE | | | | | | ROUTING | | | | | | |
| UNIT : | | | TOP SECRET | | 2 | | | | 5 | | | | |
| EXT : DATE : | | | TIP SEOULI | |] 3 | | | | 6 | | | | |
| го : | | | | | - | | | | | | | | |
| FROM: | | | | | | | | | | | | | |
| CONF: | | | | | P. R. E. | | DEFERRED | | PRIORITY | INITIA | | | |
| NFO: | | | | | RECEDENCE | | ROUTINE | \vdash | OPERATIONAL | INITIA | | | |
| • | | | | | | | | \Box | IMMEDIATE | <u> </u> | | | |
| PA | GE 3 0 | F 3. | | | | | | | | | | | |
| ·o | | | | | | | | <u> </u> | - | | | | |
| J | | | INFO | | | (| CITE | | | | | | |
| | 6. | THE | TITLING WILL INCLUDE: | | | | | | 4. | | | | |
| | | Α. | MISSION DESIGNATOR | | | | | | | | | | |
| | | В. | DATE OF PHOTOGRAPHY | | | | | | | | | | |
| | | C. | FRAME NUMBER (FIRST FRAME WILL E | E 001 | AND | ALI | FRAMES | WIL | L BE | | | | |
| | | | NUMBERED CONSECUTIVELY) | | | | | | | | | | |
| | | D. | K FACTOR (ALTITUDE) | | | | | | | | | | |
| | | E. | CLASSIFICATION | | | | | | | | | | |
| | 7. | THE | HEAD AND TAIL IDENTS WILL INCLUD | Е: | | | | | | | | | |
| | | Α. | MISSION DESIGNATOR | | | | | | | | | | |
| | | В. | PART IDENTIFER (X OF XX) | | | | | | | | | | |
| | | С. | UNIVERSAL GRID INSTRUCTION FOR 3 | 351/R | CAME | DΛ | CVCTEM (| T III: A1 | D. TDEATH | | | | |
| | | | ONLY) | 551 V 15 | Crui | IVA | OIOIIM (| ПЕА | D IDEMI | | | | |
| | | D. | CLASSIFICATION | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | Е. | HEAD OR TAIL AT EXTREME END OF I | JENT. | | | | | | | | | |
| | | | | | UNQ | UOT | E | | | | | | |

F, NPIC/TSG TOPTS COND CHIEF, NPIC/TSG/APSD AUTHENTICATING OFFICER
REPRODUCTION BY OTHER THAN THE ISSUING OFFICE IS PROHIBITED. Copy No.

Approved For Release 2008/11/24 : CIA-RDP78B03824A001100020013-9

Signal Center Transmission Copy - DO NOT DETACH - Forward with Master

CHIEF, NPIC/TSG/APSD AUTHENTICATING OFFICER

CHIEF, NPIC/TSG

25X1

25X1